



Prenett CS

The GreenEarth® Prespotter Prebrushing agent for prespotting of heavily soiled textiles, to be used with cyclosiloxane D 5 solvent, hydrocarbon or Perc.

Prenett CS TM D 18/12

Characteristics

PRENETT CS is approved by GreenEarth and recommended to be used with GreenEarth cleaning processes.

- PRENETT CS is a powerful but also gentle prespotting product with excellent cleaning and stain removal effects.
- PRENETT CS is highly concentrated and thus economical in use.
- PRENETT CS normally is used undiluted. For very delicate items PRENETT CS can be mixed 1: 1 with Cyclosiloxane D5, heavily soiled.
- PRENETT CS contains no fragrance and is free of VOC.
- PRENETT CS will flush out in Cyclosiloxane, Perc and hydrocarbon completely.
- PRENETT CS additions directly into the 1st bath of the dry cleaning process will increase the cleaning effect on heavily soiled textiles.

Chemical-physical data

Appearance	Clear, colourless liquid
Density	0.92 g/ml, 20 °C (68 °F)
Viscosity	60 - 90 mPas 20 °C (68 °F)
Flashpoint	> 100 °C (212 °F)
Effect of cold	0 °C (32 °F) clear and stable, <-5 °C (0,23 °F) solid; after warming up, clear
Solubility	In Cyclosiloxane D5: 1:1 clear, 5ml/l (0.6floz/gal), clear, in hydrocarbon: 1:1 clear, 5ml/l (0.6floz/gal) clear

Application

PRENETT CS is suitable for prebrushing of textiles with care label (P) and (F). PRENETT CS can be used undiluted with prebrushing sparingly on heavily soiled areas.

We are advising against from spraying-application!

On light coloured textiles and textiles with care label gentle dry cleaning process (P) and (F) PRENETT CS should be used 1:1 mixed with solvent. For example: cyclosiloxane 1:1 or hydrocarbon 1:1.

Intensive coloured textiles such as silk, viscose, micro fibres or acetate are very delicate and should not be prespotted.

Advice

Prespotted areas after use of PRENETT A-B-C / CS if possible use compressed air; alternatively cover with PRENETT CS 1:1 with the corresponding solvent (Cyclosiloxane D5 or hydrocarbon).

1st bath

Additions of PRENETT CS into the prewash will increase the cleaning effect. We recommend the addition of 0, 5–0,7% PRENETT CS per weight of the load for heavily soiled, insensitive loads.

Non-distilling machines

If PRENETT CS is used as prespotting agent regularly, further dosage of CLIP CSL is not necessary.

Storage and dispatch

In closed containers PRENETT CS has a minimum shelf life of 24 months.

The product is not sensitive to frost.

For ease of handling the temperature should be 15– 25 °C (59-77 °F).

Standard packagings	Dispatch unit / pallet
22 kg Plastic Canister	36